

NOTES:

- 1) FUNCTION: PASSAGE AND PRIVACY.
- 2) DIMENSION "X" AND "Y" ARE VARIABLE DEPENDING ON DOOR THICKNESS.
- 3) CURVED STRIKE EXTENSION BEYOND JAMB AT "Z" MUST NOT BE LESS THAN 3/16" (5mm) TO ENSURE PROPER FUNCTIONING OF LATCHBOLT.
- 4) STRIKE LOCATION ON FRAMES MUST BE ADJUSTED FOR THICKNESS OF DOOR SILENCERS WHEN USED.
- 5) RIGHT HAND SHOWN; FOR OPPOSITE HANDING, MIRROR DIMENSIONS TO OTHER SIDE OF JAMB.
- 6) DUST BOX CAVITY.

Description:
TSTK1 T-STRIKE FRAME PREP.
 (RIGHT HAND SHOWN)



TOLERANCES UNLESS OTHERWISE SPECIFIED:
 X.X (METRIC)= ±0.5
 X.XX(METRIC)= ±0.15
 0.00"(UNIFIED)= ±.015"
 0.000"(UNIFIED)= ±.005"

Drawing No:
DP-303

Drawn By: **JWB**

Orig.Date: **12-12-17**

Rev. Date: **11-11-25 JWB**

Rev.: **B**

SECTION A-A
 DOOR FRAME SECTION

