

- NOTES:
- 1) FUNCTION: PASSAGE AND PRIVACY.
  - 2) DIMENSION "X" AND "Y" ARE VARIABLE DEPENDING ON DOOR THICKNESS.
  - 3) CURVED STRIKE EXTENSION BEYOND JAMB AT "Z" MUST NOT BE LESS THAN 3/16" (5mm) TO ENSURE PROPER FUNCTIONING OF LATCHBOLT.
  - 4) STRIKE LOCATION ON FRAMES MUST BE ADJUSTED FOR THICKNESS OF DOOR SILENCERS WHEN USED.
  - 5) RIGHT HAND SHOWN; FOR OPPOSITE HANDING, MIRROR DIMENSIONS TO OTHER SIDE OF JAMB.

Description:  
**TSTK2 FULL LIP STRIKE FRAME PREP.**  
**ROUNDED CORNERS**



TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 X.X (METRIC)= ±0.5  
 X.XX(METRIC)= ±0.15  
 0.00"(UNIFIED)= ±.015"  
 0.000"(UNIFIED)= ±.005"

Drawing No: <b>DP-327</b>	
Drawn By:	JWB
Orig.Date	04-26-18
Rev. Date:	02-25-22
Rev.:	A

SECTION A-A  
 DOOR FRAME SECTION

