

NOTES:

- 1) FUNCTION: PASSAGE AND PRIVACY.
- 2) DIMENSION "X" AND "Y" ARE VARIABLE DEPENDING ON DOOR THICKNESS.
- 3) CURVED STRIKE EXTENSION BEYOND JAMB AT "Z" MUST NOT BE LESS THAN 3/16" (5mm) TO ENSURE PROPER FUNCTIONING OF LATCHBOLT.
- 4) STRIKE LOCATION ON FRAMES MUST BE ADJUSTED FOR THICKNESS OF DOOR SILENCERS WHEN USED.
- 5) FOR OPPOSITE HANDING, MIRROR DIMENSIONS TO OTHER SIDE OF JAMB.

Description:
**FULL LIP, SQUARE CORNER STRIKE
 PREP. GUIDE (RIGHT HAND SHOWN)**



TOLERANCES UNLESS OTHERWISE SPECIFIED:
 X.X (METRIC)= ±0.5
 X.XX(METRIC)= ±0.15
 0.00"(UNIFIED)= ±.015"
 0.000"(UNIFIED)= ±.005"

Drawing No: DP-344	
Drawn By:	JWB
Orig.Date	02-20-20
Rev. Date:	Rev.:

SECTION A-A
 DOOR FRAME SECTION

