

- NOTES:
- 1) TEMPLATE IS "NOT TO SCALE". DO NOT USE AS A MARKING TEMPLATE.
 - 2) USE APPROPRIATE DRILL DIAMETER FOR SPECIFIC DOOR MATERIAL--SEE CHART.
 - 3) FOR BACK-TO-BACK, SINGLE SIDE OR DOUBLE GLAZED DOOR PULLS, THROUGH BOLT APPLICATIONS.
 - 4) FOR SINGLE SIDE CONCEALED, PRE-DRILL APPROPRIATE HOLE ACCORDING TO SUPPLIED WOOD THREAD FASTENER. DRILL ONE SIDE OF DOOR ONLY.
 - 5) LOCATION OF HOLES DETERMINED BY GENERAL CONTRACTOR.
 - 6) HEAVY DUTY OPTION: M10 FASTENER

Description:
DOOR PREP GUIDE FOR TYPICAL "DP" SERIES DOOR PULLS



TOLERANCES UNLESS OTHERWISE SPECIFIED:
 X.X (METRIC)= ±0.5
 X.XX(METRIC)= ±0.15
 0.00"(UNIFIED)= ±.015"
 0.000"(UNIFIED)= ±.005"

Drawing No: DP-360	
Drawn By:	JWB
Orig.Date	10-23-19
Rev. Date:	12-23-25 JDK
Rev.:	F

TABLE			
TEMPLATE NO.	DIM "A" CTC	DIM "B" STANDARD OPTION (M8)	DIM "C" HEAVY DUTY OPTION (M10)
DP-360	PER ORDER	GLASS 1/2" (13mm)	GLASS 5/8" (16mm)
DP-360	PER ORDER	DOUBLE GLAZED 5/8" (16mm)	DOUBLE GLAZED 5/8" (16mm)
DP-360	PER ORDER	WOOD 3/8" (10mm)	WOOD 7/16" (11mm)

STANDARD OPTION

HEAVY DUTY OPTION

(SEE NOTE 6)

