



Contemporary Deadbolts

D500 Series Square Deadbolt






Standard Specifications	
Door Prep	Cross bore: 2-1/8" Edge bore: 1" Latch face: 1" x 2-1/4"
Backset	Fits 2-3/8" and 2-3/4"
Door Thickness	1-3/8" ~ 1-3/4" door standard
Cylinder	SC Keyway 6-pin Standard
Latches	2-3/8" and 2-3/4" available Faceplate: 1" x 2-1/4" Bolt: Full 1" throw
Base Material	Solid Brass Construction
Strikes	1-1/8" x 2-3/4" Includes Reinforcement Strike
Wood Screws	Combination screws that suit both wood and metal door mounting
Door Handing	Required on D540

Functions				
Outside	Inside	Model	Type	Description
		D520	Single Cylinder	Key Outside and Thumbturn Inside
		D540	Privacy	Thumbturn Inside and Visual Occupancy Indicator with Cointurn Outside
		D545	Privacy	Thumbturn Inside and Cointurn Outside

D600 Series Round Deadbolt



Standard Specifications	
Door Prep	Cross bore: 2-1/8" Edge bore: 1" Latch face: 1" x 2-1/4"
Backset	Fits 2-3/8" and 2-3/4"
Door Thickness	1-3/8" ~ 1-3/4" door standard
Cylinder	SC Keyway 6-pin Standard
Latches	2-3/8" and 2-3/4" available Faceplate: 1" x 2-1/4" Bolt: Full 1" throw
Base Material	Solid Brass Construction
Strikes	1-1/8" x 2-3/4" Includes Reinforcement Strike
Wood Screws	Combination screws that suit both wood and metal door mounting
Door Handing	Required on the D640

Functions				
Outside	Inside	Model	Type	Description
		D620	Single Cylinder	Key Outside and Thumbturn Inside
		D640	Privacy	Thumbturn Inside and Visual Occupancy Indicator with Cointurn Outside
		D645	Privacy	Thumbturn Inside and Cointurn Outside